

Flavor West Manufacturing, LLC.

Version No: 1.1 Safety Data Sheet according OSHA HazCom Standard (2012) requirements Chemwatch Hazard Alert Code: 4

Issue Date: 02/03/2021 Print Date: 02/03/2021 L.GHS.USA.EN

### **SECTION 1 Identification**

#### **Product Identifier**

Product name	FW-DRA N&A Dragon Fruit Flavor	
Synonyms	Not Available	
Proper shipping name	Extracts, flavoring, liquid	
Other means of identification	Not Available	

#### Recommended use of the chemical and restrictions on use

Relevant identified uses Use according to manufacturer's directions.	Relevant identified uses	Use according to manufacturer's directions.
--	--------------------------	---

#### Name, address, and telephone number of the chemical manufacturer, importer, or other responsible party

Registered company name	Flavor West Manufacturing, LLC.		
Address	0400 Hunco Way, Lake Elsinore CA 92530 United States		
Telephone	51) 893-5120		
Fax	(714) 276-1621		
Website	www.FlavorWest.com		
Email	Flavor@FlavorWest.com		

#### **Emergency phone number**

Association / Organisation	Chemwatch	CHEMWATCH EMERGENCY RESPONSE
Emergency telephone numbers	see below	+61 2 9186 1132
Other emergency telephone numbers	see below	+1 855-237-5573

Once connected and if the message is not in your prefered language then please dial 01

Una vez conectado y si el mensaje no está en su idioma preferido, por favor marque 02

#### SECTION 2 Hazard(s) identification

#### Classification of the substance or mixture

NFPA 704 diamond



Note: The hazard category numbers found in GHS classification in section 2 of this SDSs are NOT to be used to fill in the NFPA 704 diamond. Blue = Health Red = Fire Yellow = Reactivity White = Special (Oxidizer or water reactive substances)

Classification	Flammable Liquid Category 3, Eye Irritation Category 2A, Skin Corrosion/Irritation Category 2		
Label elements			

Hazard pictogram(s)	
Signal word	Warning

# Hazard statement(s)

H226	Flammable liquid and vapour.
H319	Causes serious eye irritation.
H315	Causes skin irritation.

# Hazard(s) not otherwise classified

Not Applicable

# Precautionary statement(s) General

P101	If medical advice is needed, have product container or label at hand.	
P102	Keep out of reach of children.	
P103	Read label before use.	

# Precautionary statement(s) Prevention

P210	Keep away from heat/sparks/open flames/hot surfaces No smoking.		
P233	Keep container tightly closed.		
P240	Ground/bond container and receiving equipment.		
P241	Use explosion-proof electrical/ventilating/lighting/intrinsically safe equipment.		
P242	Use only non-sparking tools.		
P243	Take precautionary measures against static discharge.		
P280	Wear protective gloves/protective clothing/eye protection/face protection.		

# Precautionary statement(s) Response

P321	Specific treatment (see advice on this label).		
P362	Take off contaminated clothing and wash before reuse.		
P370+P378	In case of fire: Use alcohol resistant foam or normal protein foam for extinction.		
P305+P351+P338	IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.		
P337+P313	If eye irritation persists: Get medical advice/attention.		
P302+P352	IF ON SKIN: Wash with plenty of water.		
P303+P361+P353	IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.		
P332+P313	If skin irritation occurs: Get medical advice/attention.		

### Precautionary statement(s) Storage

P403+P235 Store in a well-ventilated place. Keep cool.

# Precautionary statement(s) Disposal

P501

Dispose of contents/container to authorised hazardous or special waste collection point in accordance with any local regulation.

# **SECTION 3 Composition / information on ingredients**

#### Substances

See section below for composition of Mixtures

#### Mixtures

CAS No	%[weight]	Name
57-55-6	40-50	propylene glycol
64-17-5	10-20	ethanol
7732-18-5	10-20	water

The specific chemical identity and/or exact percentage (concentration) of composition has been withheld as a trade secret.

# **SECTION 4 First-aid measures**

### Description of first aid measures

Eye Contact	<ul> <li>If this product comes in contact with the eyes:</li> <li>Wash out immediately with fresh running water.</li> <li>Ensure complete irrigation of the eye by keeping eyelids apart and away from eye and moving the eyelids by occasionally lifting the upper and lower lids.</li> <li>Seek medical attention without delay; if pain persists or recurs seek medical attention.</li> <li>Removal of contact lenses after an eye injury should only be undertaken by skilled personnel.</li> </ul>
Skin Contact	<ul> <li>If skin contact occurs:</li> <li>Immediately remove all contaminated clothing, including footwear.</li> <li>Flush skin and hair with running water (and soap if available).</li> <li>Seek medical attention in event of irritation.</li> </ul>
Inhalation	<ul> <li>If fumes, aerosols or combustion products are inhaled remove from contaminated area.</li> <li>Other measures are usually unnecessary.</li> </ul>
Ingestion	<ul> <li>Immediately give a glass of water.</li> <li>First aid is not generally required. If in doubt, contact a Poisons Information Centre or a doctor.</li> </ul>

#### Most important symptoms and effects, both acute and delayed

See Section 11

#### Indication of any immediate medical attention and special treatment needed

Treat symptomatically.

- ▶ Polyethylene glycols are generally poorly absorbed orally and are mostly unchanged by the kidney.
- Dermal absorption can occur across damaged skin (e.g. through burns) leading to increased osmolality, anion gap metabolic acidosis, elevated calcium, low ionised calcium, CNS depression and renal failure.
- Treatment consists of supportive care.

[Ellenhorn and Barceloux: Medical Toxicology]

Propylene glycol is primarily a CNS depressant in large doses and may cause hypoglycaemia, lactic acidosis and seizures.

The usual measures are supportive care and decontamination (lpecac/ lavage/ activated charcoal/ cathartics), within 2 hours of exposure should suffice.
 Check the anion gap, arterial pH, renal function and glucose levels.

Ellenhorn and Barceloux: Medical Toxicology

# **SECTION 5 Fire-fighting measures**

#### Extinguishing media

- Alcohol stable foam.
- Dry chemical powder.
- BCF (where regulations permit).
- Carbon dioxide.

#### Special hazards arising from the substrate or mixture

Fire Incompatibility Avoid contamination with oxidising agents i.e. nitrates, oxidising acids, chlorine bleaches, pool chlorine etc. as ignition may result

#### Special protective equipment and precautions for fire-fighters

Fire Fighting

	<ul> <li>May be violently or explosively reactive.</li> <li>Wear breathing apparatus plus protective gloves.</li> <li>Prevent, by any means available, spillage from entering drains or water course.</li> </ul>
Fire/Explosion Hazard	<ul> <li>Liquid and vapour are flammable.</li> <li>Moderate fire hazard when exposed to heat or flame.</li> <li>Vapour forms an explosive mixture with air.</li> <li>Moderate explosion hazard when exposed to heat or flame.</li> <li>Combustion products include:</li> <li>carbon monoxide (CO)</li> <li>carbon dioxide (CO2)</li> <li>other pyrolysis products typical of burning organic material.</li> </ul>

# **SECTION 6 Accidental release measures**

# Personal precautions, protective equipment and emergency procedures

See section 8

# **Environmental precautions**

See section 12

# Methods and material for containment and cleaning up

Minor Spills	<ul> <li>Remove all ignitior</li> <li>Clean up all spills i</li> <li>Avoid breathing va</li> <li>Control personal c</li> </ul>	mmediately. pours and cor			-		ent.
	Chemical Class: alcohols and glycols For release onto land: recommended sorbents listed in order of priority.						
	TYPE RANK APPLICATIO		N	COLLE	CTION I	LIMITATIONS	
	LAND SPILL - SMALL	-					
	cross-linked polymer	- particulate	1	shovel	shovel	R, W, SS	
	cross-linked polymer	- pillow	1	throw	pitchfork	R, DGC, RT	
	sorbent clay - particu	ate	2	shovel	shovel	R,I, P	
	wood fiber - pillow		3		-	R, P, DGC, RT	
	treated wood fiber - pillow		3	throw	•	DGC, RT	
	foamed glass - pillow		4	throw	pichfork	R, P, DGC, RT	
	LAND SPILL - MEDIUM						
	cross-linked polymer - particulate		1	blower	skiploade	er R,W, SS	
Major Spills	polypropylene - particulate		2	blower	skiploade	er W, SS, DGC	
	sorbent clay - particulate		2	blower	skiploade	er R, I, W, P, DGC	>
	polypropylene - mat		3	throw	skiploade	er DGC, RT	
	expanded mineral - particulate		3	blower	skiploade	er R, I, W, P, DGC	<u>}</u>
	polyurethane - mat		4	throw	skiploade	er DGC, RT	
	Legend DGC: Not effective wh R; Not reusable I: Not incinerable P: Effectiveness reduc RT:Not effective where SS: Not for use within W: Effectiveness reduc Reference: Sorbents f R.W Melvold et al: Pol • Clear area of person • Alert Fire Brigade a • May be violently on • Wear breathing ap	ed when rainy e terrain is rug environmenta ced when wind for Liquid Haz lution Technol ponnel and mov and tell them I	/ geo lly arc log ve l loca eac	d lous Suba y Review upwind. ation and ctive.	sites stance Cle No. 150: nature of	Noyes Data Corpo	

Personal Protective Equipment advice is contained in Section 8 of the SDS.

# **SECTION 7 Handling and storage**

# Precautions for safe handling

Safe handling	<ul> <li>Containers, even those that have been emptied, may contain explosive vapours.</li> <li>Do NOT cut, drill, grind, weld or perform similar operations on or near containers.</li> <li>Avoid all personal contact, including inhalation.</li> <li>Wear protective clothing when risk of overexposure occurs.</li> <li>Use in a well-ventilated area.</li> <li>Prevent concentration in hollows and sumps.</li> <li>DO NOT allow clothing wet with material to stay in contact with skin</li> </ul>
Other information	<ul> <li>Consider storage under inert gas.</li> <li>Store in original containers in approved flammable liquid storage area.</li> <li>Store away from incompatible materials in a cool, dry, well-ventilated area.</li> <li>DO NOT store in pits, depressions, basements or areas where vapours may be trapped.</li> <li>No smoking, naked lights, heat or ignition sources.</li> </ul>

# Conditions for safe storage, including any incompatibilities

Suitable container	<ul> <li>Packing as supplied by manufacturer.</li> <li>Plastic containers may only be used if approved for flammable liquid.</li> <li>Check that containers are clearly labelled and free from leaks.</li> <li>For low viscosity materials (i) : Drums and jerry cans must be of the non-removable head type. (ii) : Where a can is to be used as an inner package, the can must have a screwed enclosure.</li> <li>For materials with a viscosity of at least 2680 cSt. (23 deg. C)</li> <li>For manufactured product having a viscosity of at least 250 cSt.</li> </ul>
Storage incompatibility	<ul> <li>Glycols and their ethers undergo violent decomposition in contact with 70% perchloric acid. This seems likely to involve formation of the glycol perchlorate esters (after scission of ethers) which are explosive, those of ethylene glycol and 3-chloro-1,2-propanediol being more powerful than glyceryl nitrate, and the former so sensitive that it explodes on addition of water.</li> <li>Alcohols <ul> <li>are incompatible with strong acids, acid chlorides, acid anhydrides, oxidising and reducing agents.</li> <li>reacts, possibly violently, with alkaline metals and alkaline earth metals to produce hydrogen</li> <li>react with strong acids, strong caustics, aliphatic amines, isocyanates, acetaldehyde, benzoyl peroxide, chromic acid, chromium oxide, dialkylzincs, dichlorine oxide, ethylene oxide, hypochlorous acid, isopropyl chlorocarbonate, lithium tetrahydroaluminate, nitrogen dioxide, pentafluoroguanidine, phosphorus halides, phosphorus pentasulfide, tangerine oil, triethylaluminium, triisobutylaluminium</li> <li>should not be heated above 49 deg. C. when in contact with aluminium equipment</li> </ul> </li> </ul>

# **SECTION 8 Exposure controls / personal protection**

# **Control parameters**

# Occupational Exposure Limits (OEL)

# INGREDIENT DATA

Source	Ingredient	Material name	TWA	STEL	Peak	Notes
US NIOSH Recommended Exposure Limits (RELs)	ethanol	Alcohol, Cologne spirit, Ethanol, EtOH, Grain alcohol	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available
US OSHA Permissible Exposure Levels (PELs) - Table Z1	ethanol	Ethyl alcohol (Ethanol)	1000 ppm / 1900 mg/m3	Not Available	Not Available	Not Available
US ACGIH Threshold Limit Values (TLV)	ethanol	Ethanol	Not Available	1000 ppm	Not Available	URT irr

#### **Emergency Limits**

propylene glycol Polypropy				
рторутеле длусот Ротуртору	ylene glycols	30 mg/m3	330 mg/m3	2,000 mg/m3
propylene glycol Propylene	e glycol; (1,2-Propanediol)	30 mg/m3	1,300 mg/m3	7,900 mg/m3
ethanol Ethanol: (	(Ethyl alcohol)	Not Available	Not Available	15000* ppm

Ingredient	Original IDLH	Revised IDLH
propylene glycol	Not Available	Not Available
ethanol	3,300 ppm	Not Available
water	Not Available	Not Available

### Occupational Exposure Banding

Ingredient	Occupational Exposure Band Rating	Occupational Exposure Band Limit	
propylene glycol	E	≤ 0.1 ppm	
Notes:	Occupational exposure banding is a process of assigning chemicals into specific categories or bands based on a chemical's potency and the adverse health outcomes associated with exposure. The output of this process is an occupational exposure band (OEB), which corresponds to a range of exposure concentrations that are expected to protect worker health.		

# MATERIAL DATA

For ethanol:

Odour Threshold Value: 49-716 ppm (detection), 101 ppm (recognition)

Eye and respiratory tract irritation do not appear to occur at exposure levels of less than 5000 ppm and the TLV-TWA is thought to provide an adequate margin of safety against such effects. Experiments in man show that inhalation of 1000 ppm caused slight symptoms of poisoning and 5000 ppm caused strong stupor and morbid sleepiness. Subjects exposed to 5000 ppm to 10000 ppm experienced smarting of the eyes and nose and coughing. Symptoms disappeared within minutes.

for propylene glycol:

Saturated vapour concentration @ 20 deg C.= 65.8 ppm, 204.6 mg/m3; i.e higher concentrations can only occur as aerosols or at higher temperatures. Odour Threshold: Practically odourless.

A small number of individuals show skin irritation or sensitisation from repeated or prolonged exposure to propylene glycol. A workplace environmental exposure limit (WEEL) has been established by AIHA and is thought to be protective against systemic effects.

#### **Exposure controls**

Appropriate engineering controls	Engineering controls are used to remove a hazard or place a barrier between the worker and the hazard. Well-designed engineering controls can be highly effective in protecting workers and will typically be independent of worker interactions to provide this high level of protection. The basic types of engineering controls are: Process controls which involve changing the way a job activity or process is done to reduce the risk. Enclosure and/or isolation of emission source which keeps a selected hazard "physically" away from the worker and ventilation that strategically "adds" and "removes" air in the work environment.
Personal protection	
Eye and face protection	<ul> <li>Safety glasses with side shields.</li> <li>Chemical goggles.</li> <li>Contact lenses may pose a special hazard; soft contact lenses may absorb and concentrate irritants. A written policy document, describing the wearing of lenses or restrictions on use, should be created for each workplace or task.</li> </ul>
Skin protection	See Hand protection below
Hands/feet protection	<ul> <li>Wear chemical protective gloves, e.g. PVC.</li> <li>Wear safety footwear or safety gumboots, e.g. Rubber</li> <li>The selection of suitable gloves does not only depend on the material, but also on further marks of quality which vary from manufacturer to manufacturer. Where the chemical is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.</li> <li>The exact break through time for substances has to be obtained from the manufacturer of the protective gloves and has to be observed when making a final choice.</li> <li>Personal hygiene is a key element of effective hand care.</li> </ul>
Body protection	See Other protection below
Other protection	<ul> <li>Employees working with confirmed human carcinogens should be provided with, and be required to wear, clean, full body protective clothing (smocks, coveralls, or long-sleeved shirt and pants), shoe covers and gloves prior to entering the regulated area. [AS/NZS ISO 6529:2006 or national equivalent]</li> <li>Employees engaged in handling operations involving carcinogens should be provided with, and required to wear and use half-face filter-type respirators with filters for dusts, mists and fumes, or air purifying canisters or cartridges. A respirator affording higher levels of protection may be substituted. [AS/NZS 1715 or national equivalent]</li> <li>Emergency deluge showers and eyewash fountains, supplied with potable water, should be located near, within sight of, and on the same level with locations where direct exposure is likely.</li> <li>Prior to each exit from an area containing confirmed human carcinogens, employees should be required to remove and leave protective clothing and equipment at the point of exit and at the last exit of the day, to place used clothing and equipment in impervious containers at the point of exit for purposes of decontamination or disposal. The contents of such impervious containers must be identified with suitable labels. For maintenance and decontamination activities, authorized employees</li> </ul>

entering the area should be provided with and required to wear clean, impervious garments, including gloves, boots and continuous-air supplied hood.

- Prior to removing protective garments the employee should undergo decontamination and be required to shower upon removal of the garments and hood.
- Overalls.
- PVC Apron
- PVC protective suit may be required if exposure severe.
- Eyewash unit.
- Some plastic personal protective equipment (PPE) (e.g. gloves, aprons, overshoes) are not recommended as they may produce static electricity.
- + For large scale or continuous use wear tight-weave non-static clothing (no metallic fasteners, cuffs or pockets).
- Non sparking safety or conductive footwear should be considered. Conductive footwear describes a boot or shoe with a sole made from a conductive compound chemically bound to the bottom components, for permanent control to electrically ground the foot an shall dissipate static electricity from the body to reduce the possibility of ignition of volatile compounds.

#### Recommended material(s)

#### GLOVE SELECTION INDEX

Glove selection is based on a modified presentation of the:

"Forsberg Clothing Performance Index".

The effect(s) of the following usbstance(s) are taken into account in the

computer-generated selection:

FW-DRA N&A Dragon Fruit Flavor

Material	CPI
BUTYL	С
NATURAL RUBBER	С
NATURAL+NEOPRENE	С
NEOPRENE	С
NITRILE	С
NITRILE+PVC	С
PE/EVAL/PE	С
PVA	С
PVC	С
VITON	С

\* CPI - Chemwatch Performance Index

A: Best Selection

B: Satisfactory; may degrade after 4 hours continuous immersion

C: Poor to Dangerous Choice for other than short term immersion

**NOTE:** As a series of factors will influence the actual performance of the glove, a final selection must be based on detailed observation. -

\* Where the glove is to be used on a short term, casual or infrequent basis.

factors such as "feel" or convenience (e.g. disposability), may dictate a choice of gloves which might otherwise be unsuitable following long-term or frequent use. A qualified practitioner should be consulted.

#### **SECTION 9** Physical and chemical properties

#### Information on basic physical and chemical properties

# Respiratory protection

Type A Filter of sufficient capacity. (AS/NZS 1716 & 1715, EN 143:2000 & 149:2001, ANSI Z88 or national equivalent)

Where the concentration of gas/particulates in the breathing zone, approaches or exceeds the "Exposure Standard" (or ES), respiratory protection is required.

Degree of protection varies with both face-piece and Class of filter; the nature of protection varies with Type of filter.

Required Minimum Protection Factor up to 5 x ES	Half-Face Respirator Air-line*	Full-Face Respirator A-2	Powered Air Respirator A-PAPR-2 ^
up to 10 x ES	-	A-3	-
10+ x ES	-	Air-line**	-

\* - Continuous Flow; \*\* - Continuous-flow or positive pressure demand ^ - Full-face

A(All classes) = Organic vapours, B AUS or B1 = Acid gasses, B2 = Acid gas or hydrogen cyanide(HCN), B3 = Acid gas or hydrogen cyanide(HCN), E = Sulfur dioxide(SO2), G = Agricultural chemicals, K = Ammonia(NH3), Hg = Mercury, NO = Oxides of nitrogen, MB = Methyl bromide, AX = Low boiling point organic compounds(below 65 degC)

- Cartridge respirators should never be used for emergency ingress or in areas of unknown vapour concentrations or oxygen content.
- The wearer must be warned to leave the contaminated area immediately on detecting any odours through the respirator. The odour may indicate that the mask is not functioning properly, that the vapour concentration is too high, or that the mask is not properly fitted. Because of these limitations, only restricted use of cartridge respirators is considered appropriate.
- Cartridge performance is affected by humidity. Cartridges should be changed after 2 hr of continuous use unless it is determined that the humidity is less than 75%, in which case, cartridges can be used for 4 hr. Used cartridges should be discarded daily, regardless of the length of time used

Appearance	Clear pink to red		
		Relative density (Water =	
Physical state	Liquid	(Water = 1)	1.10
Odour	Characteristic	Partition coefficient n-octanol / water	Not Available
Odour threshold	Not Available	Auto-ignition temperature (°C)	Not Available
pH (as supplied)	Not Available	Decomposition temperature	Not Available
Melting point / freezing point (°C)	Not Available	Viscosity (cSt)	Not Available

Initial boiling point and boiling range (°C)	Not Available	Molecular weight (g/mol)	Not Available
Flash point (°C)	42.5	Taste	Dragon fruit
Evaporation rate	Not Available	Explosive properties	Not Available
Flammability	Flammable.	Oxidising properties	Not Available
Upper Explosive Limit (%)	Not Available	Surface Tension (dyn/cm or mN/m)	Not Available
Lower Explosive Limit (%)	Not Available	Volatile Component (%vol)	Not Available
Vapour pressure (kPa)	Not Available	Gas group	Not Available
Solubility in water	Miscible	pH as a solution (1%)	Not Available
Vapour density (Air = 1)	Not Available	VOC g/L	Not Available

# **SECTION 10 Stability and reactivity**

Reactivity	See section 7
Chemical stability	<ul> <li>Unstable in the presence of incompatible materials.</li> <li>Product is considered stable.</li> <li>Hazardous polymerisation will not occur.</li> </ul>
Possibility of hazardous reactions	See section 7
Conditions to avoid	See section 7
Incompatible materials	See section 7
Hazardous decomposition products	See section 5

# **SECTION 11 Toxicological information**

# Information on toxicological effects

Inhaled	The material is not thought to produce adverse health effects or irritation of the respiratory tract (as classified by EC Directives using animal models). Nevertheless, good hygiene practice requires that exposure be kept to a minimum and that suitable control measures be used in an occupational setting. The most common signs of inhalation overexposure to ethanol, in animals, include ataxia, incoordination and drowsiness for those surviving narcosis. The narcotic dose for rats, after 2 hours of exposure, is 19260 ppm. Exposure to aliphatic alcohols with more than 3 carbons may produce central nervous system effects such as headache, dizziness, drowsiness, muscle weakness, delirium, CNS depression, coma, seizure, and neurobehavioural changes. Symptoms are more acute with higher alcohols. Respiratory tract involvement may produce irritation of the mucosa, respiratory insufficiency, respiratory depression secondary to CNS depression, pulmonary oedema, chemical pneumonitis and bronchitis. Cardiovascular involvement may result in arrhythmias and hypotension. Inhalation hazard is increased at higher temperatures. Inhalation of vapours or aerosols (mists, fumes), generated by the material during the course of normal handling, may be damaging to the health of the individual.		
	Ingestion of ethan Blood concentration:	nol may produce nausea, vomiting, gastrointestinal bleeding, abdominal pain and diarrhoea. Systemic effects:	
	<1.5 g/l	Mild: Impaired visual acuity, coordination and reaction time, emotional lability	
Ingestion	1.5-3.0 g/l	Moderate: Slurred speech, confusion, ataxia, emotional lability, perceptual and sensation disturbances possible blackout spells, and incoordination with impaired objective performance in standardised tests. Possible diplopia, flushing, tachycardia, sweating and incontinence. Bradypnoea may occur early and tachypnoea may develop in cases of metabollic acidosis, hypoglycaemia and hypokalaemia.	
	Symptoms includ child who ingeste Excessive repeat individuals; this n Very high doses	ylene glycol produced reversible central nervous system depression in humans following ingestion of 60 ml. led increased heart-rate (tachycardia), excessive sweating (diaphoresis) and grand mal seizures in a 15 month ad large doses (7.5 ml/day for 8 days) as an ingredient of vitamin preparation. ted ingestions may cause hypoglycaemia (low levels of glucose in the blood stream) among susceptible nay result in muscular weakness, incoordination and mental confusion. given during feeding studies to rats and dogs produce central nervous system depression (although one-third of ethanol), haemolysis and insignificant kidney changes.	

	nervous system (CNS), nausea, vomiting and degener Effects on the nervous system characterise over-expo- weakness, giddiness, ataxia, (loss of muscle coordinat nausea, vomiting and diarrhoea. In the absence of effe animals acutely poisoned by the higher alcohols. The material has <b>NOT</b> been classified by EC Directive of the lack of corroborating animal or human evidence following ingestion, especially where pre-existing organ	sure to higher aliphatic alcohols. These include headache, muscle ion), confusion, delirium and coma. Gastrointestinal effects may include active treatment, respiratory arrest is the most common cause of death in s or other classification systems as "harmful by ingestion". This is because The material may still be damaging to the health of the individual, n (e.g liver, kidney) damage is evident. Present definitions of harmful or ing mortality rather than those producing morbidity (disease, ill-health).	
Skin Contact	<ul> <li>health damage following entry through wounds, lesion: A single prolonged exposure is not likely to result in the be absorbed in potentially harmful amounts when appl areas of the body as part of a cream, other topical app material. Absorption under such circumstances can ele Most liquid alcohols appear to act as primary skin irritanot apparently in man.</li> <li>Open cuts, abraded or irritated skin should not be expenditure to the blood-stream through, for example, cuts harmful effects. Examine the skin prior to the use of the material produces moderate skin irritation; eviden b produces significant, but moderate, inflammation w such inflammation being present twenty-four hours.</li> <li>Skin irritation may also be present after prolonged or information.</li> </ul>	ts (as classified under EC Directives); the material may still produce s or abrasions. e material being absorbed in harmful amounts. However the material may ied in large quantities to severe burns (second or third degree) over large lication or by prolonged contact with clothing accidentally wetted by the evated serum osmolality and may result in osmotic shock. Ints in humans. Significant percutaneous absorption occurs in rabbits but osed to this material abrasions, puncture wounds or lesions, may produce systemic injury with e material and ensure that any external damage is suitably protected. ce exists, or practical experience predicts, that the material either ubstantial number of individuals following direct contact, and/or then applied to the healthy intact skin of animals (for up to four hours), or more after the end of the exposure period. repeated exposure; this may result in a form of contact dermatitis skin redness (erythema) and swelling (oedema) which may progress to upidermis. At the microscopic level there may be intercellular oedema of	
Eye	Direct contact of the eye with ethanol may cause immediate stinging and burning with reflex closure of the lid and tearing, transient injury of the corneal epithelium and hyperaemia of the conjunctiva. Foreign-body type discomfort may persist for up to 2 days but healing is usually spontaneous and complete. Irritation of the eyes may produce a heavy secretion of tears (lachrymation). Limited evidence or practical experience suggests, that the material may cause eye irritation in a substantial number of individuals. Repeated or prolonged eye contact may cause inflammation characterised by temporary redness (similar to windburn) of the conjunctiva (conjunctivitis); temporary impairment of vision and/or other transient eye damage/ulceration may occur.		
Chronic	On the basis of epidemiological data, the material is regarded as carcinogenic to humans. There is sufficient data to establish a causal association between human exposure to the material and the development of cancer. Toxic: danger of serious damage to health by prolonged exposure through inhalation, in contact with skin and if swallowed. Serious damage (clear functional disturbance or morphological change which may have toxicological significance) is likely to be caused by repeated or prolonged exposure. As a rule the material produces, or contains a substance which produces severe lesions. Such damage may become apparent following direct application in subchronic (90 day) toxicity studies or following sub-acute (28 day) or chronic (two-year) toxicity tests. Long-term exposure to ethanol may result in progressive liver damage with fibrosis or may exacerbate liver injury caused by other agents. Repeated ingestion of ethanol by pregnant women may adversely affect the central nervous system of the developing foetus, producing effects collectively described as foetal alcohol syndrome. These include mental and physical retardation, learning disturbances, motor and language deficiency, behavioural disorders and reduced head size. Consumption of ethanol (in alcoholic beverages) may be linked to the development of Type I hypersensitivities in a small number of individuals.		
FW-DRA N&A Dragon	ΤΟΧΙΟΙΤΥ	IRRITATION	
Fruit Flavor	Not Available	Not Available	
	ΤΟΧΙΟΙΤΥ	IRRITATION	
	Dermal (rabbit) LD50: >2000 mg/kg <sup>[1]</sup>	Eye (rabbit): 100 mg - mild	

propylene glycol

Inhalation(Rat) LC50; >44.9 mg/L4hrs<sup>[2]</sup>

Oral(Rat) LD50; 0.02 mg/kg<sup>[2]</sup>

Skin(human):500 mg/7days mild

Skin(human):104 mg/3d Intermit Mod

Eye (rabbit): 500 mg/24h - mild

Skin: no adverse effect observed (not irritating)<sup>[1]</sup>

Eye: no adverse effect observed (not irritating)<sup>[1]</sup>

	ΤΟΧΙΟΙΤΥ	IRRITATION
	Dermal (rabbit) LD50: >15800 mg/kg <sup>[1]</sup>	Eye (rabbit): 500 mg SEVERE
	Inhalation(Mouse) LC50; =39 mg/l4hrs <sup>[2]</sup>	Eye (rabbit):100mg/24hr-moderate
ethanol	Oral(Rat) LD50; >7692 mg/kg <sup>[1]</sup>	Eye: adverse effect observed (irritating) <sup>[1]</sup>
		Skin (rabbit):20 mg/24hr-moderate
		Skin (rabbit):400 mg (open)-mild
		Skin: no adverse effect observed (not irritating) <sup>[1]</sup>
water	ΤΟΧΙCITY	IRRITATION
water	Oral(Rat) LD50; >90 mg/kg <sup>[2]</sup>	Not Available
Legend:	<ol> <li>Value obtained from Europe ECHA Registered Substances - Acute toxicity 2.* Value obtained from manufacturer's SDS. Unless otherwise specified data extracted from RTECS - Register of Toxic Effect of chemical Substances</li> </ol>	

WATER	No significant acute toxicological data identified in literature search.	
FW-DRA N&A Dragon Fruit Flavor & PROPYLENE GLYCOL	The acute oral toxicity of propylene glycol is very low, and large quantities are requing humans. Serious toxicity generally occurs only at plasma concentrations over 1 g/L relatively short period of time. It would be nearly impossible to reach toxic levels by contain at most 1 g/kg of PG. Cases of propylene glycol poisoning are usually related administration or accidental ingestion of large quantities by children. The potential for the second se	, which requires extremely high intake over a consuming foods or supplements, which ed to either inappropriate intravenous
PROPYLENE GLYCOL & ETHANOL	The material may cause skin irritation after prolonged or repeated exposure and ma This form of dermatitis is often characterised by skin redness (erythema) and swell intercellular oedema of the spongy layer (spongiosis) and intracellular oedema of the	ing the epidermis. Histologically there may be
		•
Acute Toxicity	× Carcinogenicity	×
Acute Toxicity Skin Irritation/Corrosion	× Carcinogenicity < Reproductivity	×
Skin Irritation/Corrosion Serious Eye	Reproductivity	×

#### Data available to make classification

# **SECTION 12 Ecological information**

	Endpoint	Test Duration (hr)		Species		Value	Source
FW-DRA N&A Dragon Fruit Flavor	Not Available	Not Available		Not Available		Not Available	Not Availabl
	Endpoint	Test Duration (hr)		Species		Value	Sourc
	LC50	96		Fish		710-mg/L	4
propylene glycol	EC50	48		Crustacea		>110mg/L	4
	EC50	96		Algae or other aquatic plants		19000mg/L	2
	NOEC	168		Fish		98-mg/L	4
	Endpoint	Test Duration (hr)	Sp	ecies	Value	•	Source
	LC50	96	Fis	h	42-m	g/L	4
a the second	EC50	48	Cru	istacea	2-mg	/L	4
ethanol	EC50	96	Alg	ae or other aquatic plants	-8.35	8-26.503mg/L	4
	EC10	168	Alg	ae or other aquatic plants	1.91-	mg/L	4
	NOEC	2016	Fis	h	0.000	)375-mg/L	4
	Endpoint	Test Duration (hr)		Species		Value	Source
water	Not Available	Not Available		Not Available		Not Available	Not Availabl

Legend:	Extracted from 1. IUCLID Toxicity Data 2. Europe ECHA Registered Substances - Ecotoxicological Information - Aquatic Toxicity
	3. EPIWIN Suite V3.12 (QSAR) - Aquatic Toxicity Data (Estimated) 4. US EPA, Ecotox database - Aquatic Toxicity Data 5.
	ECETOC Aquatic Hazard Assessment Data 6. NITE (Japan) - Bioconcentration Data 7. METI (Japan) - Bioconcentration Data 8.
	Vendor Data

When ethanol is released into the soil it readily and quickly biodegrades but may leach into ground water; most is lost by evaporation. When released into water the material readily evaporates and is biodegradable.

Ethanol does not bioaccumulate to an appreciable extent.

The material is readily degraded by reaction with photochemically produced hydroxy radicals; release into air will result in photodegradation and wet deposition. Propylene glycol is known to exert high levels of biochemical oxygen demand (BOD) during degradation in surface waters. This process can adversely affect aquatic life by consuming oxygen needed by aquatic organisms for survival. Large quantities of dissolved oxygen (DO) in the water column are consumed when microbial populations decompose propylene glycol.

Sufficient dissolved oxygen levels in surface waters are critical for the survival of fish, macro-invertebrates, and other aquatic organisms.

# Persistence and degradability

Ingredient	Persistence: Water/Soil	Persistence: Air
propylene glycol	LOW	LOW
ethanol	LOW (Half-life = 2.17 days)	LOW (Half-life = 5.08 days)
water	LOW	LOW

#### **Bioaccumulative potential**

Ingredient	Bioaccumulation
propylene glycol	LOW (BCF = 1)
ethanol	LOW (LogKOW = -0.31)
water	LOW (LogKOW = -1.38)

#### Mobility in soil

Ingredient	Mobility
propylene glycol	HIGH (KOC = 1)
ethanol	HIGH (KOC = 1)
water	LOW (KOC = 14.3)

# **SECTION 13 Disposal considerations**

	Containers may still present a chemical hazard/ danger when empty.
	Return to supplier for reuse/ recycling if possible.
	Otherwise:
	If container can not be cleaned sufficiently well to ensure that residuals do not remain or if the container cannot be used to store the same product, then puncture containers, to prevent re-use, and bury at an authorised landfill.
	Where possible retain label warnings and SDS and observe all notices pertaining to the product.
	Legislation addressing waste disposal requirements may differ by country, state and/ or territory. Each user must refer to laws
	operating in their area. In some areas, certain wastes must be tracked.
	A Hierarchy of Controls seems to be common - the user should investigate:
	▶ Reduction
	▶ Reuse
Product / Packaging	▶ Recycling
disposal	▶ Disposal (if all else fails)
	This material may be recycled if unused, or if it has not been contaminated so as to make it unsuitable for its intended use.
	DO NOT allow wash water from cleaning or process equipment to enter drains.
	It may be necessary to collect all wash water for treatment before disposal.
	In all cases disposal to sewer may be subject to local laws and regulations and these should be considered first.
	Where in doubt contact the responsible authority.
	▶ Recycle wherever possible.
	<ul> <li>Consult manufacturer for recycling options or consult local or regional waste management authority for disposal if no suitable treatment or disposal facility can be identified.</li> </ul>
	<ul> <li>Dispose of by: burial in a land-fill specifically licensed to accept chemical and / or pharmaceutical wastes or Incineration in a licensed apparatus (after admixture with suitable combustible material).</li> </ul>
	<ul> <li>Decontaminate empty containers.</li> </ul>

# **SECTION 14 Transport information**

# Labels Required



Marine Pollutant

# Land transport (DOT)

UN number	1197	
UN proper shipping name	Extracts, flavoring, lic	uid
Transport hazard class(es)	Class 3 Subrisk Not App	licable
Packing group	Ш	
Environmental hazard	Not Applicable	
Special precautions for user	Hazard Label Special provisions	3 B1, IB3, T2, TP1

# Air transport (ICAO-IATA / DGR)

UN number	1197			
UN proper shipping name	Extracts, flavouring, liquid			
Transport hazard class(es)	ICAO/IATA Class ICAO / IATA Subrisk ERG Code	3 Not Applicable 3L		
Packing group	III			
Environmental hazard	Not Applicable			
Special precautions for user		Qty / Pack Packing Instructions	A3 366 220 L 355 60 L Y344 10 L	

# Sea transport (IMDG-Code / GGVSee)

UN number	1197		
UN proper shipping name	EXTRACTS, FLAVOURING, LIQUID		
Transport hazard class(es)		3 Not Applicable	
Packing group	III		
Environmental hazard	Not Applicable		
Special precautions for user	EMS Number Special provisions Limited Quantities		

Transport in bulk according to Annex II of MARPOL and the IBC code

Not Applicable

#### Transport in bulk in accordance with MARPOL Annex V and the IMSBC Code

Product name	Group
propylene glycol	Not Available
ethanol	Not Available
water	Not Available

#### Transport in bulk in accordance with the ICG Code

Product name	Ship Type
propylene glycol	Not Available
ethanol	Not Available
water	Not Available

#### **SECTION 15 Regulatory information**

#### Safety, health and environmental regulations / legislation specific for the substance or mixture

#### propylene glycol is found on the following regulatory lists

US ATSDR Minimal Risk Levels for Hazardous Substances (MRLs)

US DOE Temporary Emergency Exposure Limits (TEELs)

US EPA Integrated Risk Information System (IRIS)

- US Toxic Substances Control Act (TSCA) Chemical Substance Inventory
- US Toxicology Excellence for Risk Assessment (TERA) Workplace Environmental Exposure Levels (WEEL)

US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### ethanol is found on the following regulatory lists

US ACGIH Threshold Limit Values (TLV)

- US ACGIH Threshold Limit Values (TLV) Carcinogens
- US AIHA Workplace Environmental Exposure Levels (WEELs)
- US DOE Temporary Emergency Exposure Limits (TEELs)
- US NIOSH Recommended Exposure Limits (RELs)
- US OSHA Permissible Exposure Levels (PELs) Table Z1

US OSHA Permissible Exposure Limits - Annotated Table Z-1

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### water is found on the following regulatory lists

US Toxic Substances Control Act (TSCA) - Chemical Substance Inventory

US TSCA Chemical Substance Inventory - Interim List of Active Substances

#### **Federal Regulations**

### Superfund Amendments and Reauthorization Act of 1986 (SARA)

#### Section 311/312 hazard categories

Flammable (Gases, Aerosols, Liquids, or Solids)	Yes
Gas under pressure	No
Explosive	No
Self-heating	No
Pyrophoric (Liquid or Solid)	No
Pyrophoric Gas	No
Corrosive to metal	No
Oxidizer (Liquid, Solid or Gas)	No
Organic Peroxide	No
Self-reactive	No
In contact with water emits flammable gas	No
Combustible Dust	No
Carcinogenicity	No

Acute toxicity (any route of exposure)	No
Reproductive toxicity	No
Skin Corrosion or Irritation	Yes
Respiratory or Skin Sensitization	No
Serious eye damage or eye irritation	Yes
Specific target organ toxicity (single or repeated exposure)	
Aspiration Hazard	No
Germ cell mutagenicity	No
Simple Asphyxiant	No
Hazards Not Otherwise Classified	No

US. EPA CERCLA Hazardous Substances and Reportable Quantities (40 CFR 302.4)

None Reported

#### **State Regulations**

#### US. California Proposition 65

None Reported

#### **National Inventory Status**

National Inventory	Status
Australia - AIIC / Australia Non-Industrial Use	Yes
Canada - DSL	Yes
Canada - NDSL	No (propylene glycol; ethanol; water)
China - IECSC	Yes
Europe - EINEC / ELINCS / NLP	Yes
Japan - ENCS	Yes
Korea - KECI	Yes
New Zealand - NZIoC	Yes
Philippines - PICCS	Yes
USA - TSCA	Yes
Taiwan - TCSI	Yes
Mexico - INSQ	Yes
Vietnam - NCI	Yes
Russia - ARIPS	Yes
Legend:	Yes = All CAS declared ingredients are on the inventory No = One or more of the CAS listed ingredients are not on the inventory and are not exempt from listing(see specific ingredients in brackets)

# **SECTION 16 Other information**

Revision Date	02/03/2021
Initial Date	02/03/2021

#### Other information

Classification of the preparation and its individual components has drawn on official and authoritative sources as well as independent review by the Chemwatch Classification committee using available literature references.

The SDS is a Hazard Communication tool and should be used to assist in the Risk Assessment. Many factors determine whether the reported Hazards are Risks in the workplace or other settings. Risks may be determined by reference to Exposures Scenarios. Scale of use, frequency of use and current or available engineering controls must be considered.

### **Definitions and abbreviations**

PC-TWA: Permissible Concentration-Time Weighted Average

PC-STEL: Permissible Concentration-Short Term Exposure Limit

IARC: International Agency for Research on Cancer

ACGIH: American Conference of Governmental Industrial Hygienists STEL: Short Term Exposure Limit TEEL: Temporary Emergency Exposure Limit。 IDLH: Immediately Dangerous to Life or Health Concentrations OSF: Odour Safety Factor NOAEL :No Observed Adverse Effect Level LOAEL: Lowest Observed Adverse Effect Level TLV: Threshold Limit Value LOD: Limit Of Detection OTV: Odour Threshold Value

BCF: BioConcentration Factors

BEI: Biological Exposure Index

Powered by AuthorITe, from Chemwatch.

